

Single sole cleaning device

Art.-Nr.: 1.560.01



Single sole cleaning device

The machine is created for boots and sides cleaning by entrance and exit. Machine is entirely made of stainless steel 1.4301 except of the mechanism. The cleaning starts with pressing the button. The boots are cleaned by horizontal brushes which is rotating. For additional cleaning injector sprays boot with water and detergent.

The canister can be put into the holder. The water supply and outlet must be set from customers The machines are according to EU-guidelines /Council Directives Nr. 2006/42/EC and 2006/95/EC and the USDA-Regulations

F&L GmbH Partner für Hygiene & FördertechnikLindenpark 16Tel: 033652-82280D- 15898 Neuzellewww.flnet.dewww.flnet.deFax: 033652-822827info@flnet.deFax: 033652-822827





Art.-Nr.: 1.560.01


technical data:

voltage control: net frequency: voltage control: performance: protection type: water supply: water outlet: cleaning time: temperature: weigth: dimensions: total length: width: heigth: cleaning surface: 400 V 50 Hz 24 V DC 0.25 KW IP 65 R 1/2" HT- pipe DN 50 5-10 s/ sole min. 4°C, max. 40°C ca. 40 Kg

855 mm 624 mm 1.065 mm length: 420 mm







F&L GmbH Partner für Hygiene & Fördertechnik Lindenpark 16

D-15898 Neuzelle www.flnet.de info@flnet.de

Tel: 033652-82280

Fax: 033652-822827