

Single boot cleaning device

Art.-Nr.: 1.560.02



Single sole cleaning

The machine is created for boots and sides cleaning by entrance and exit. Machine is entirely made of stainless steel 1.4301 except of the mechanism. The cleaning starts with pressing the button. The boots are cleaned by horizontal brush which is rotating. For additional cleaning injector sprays boot with water and detergent.

The canister can be put into the holder. The water supply and outlet must be set from customers The machines are according to EU-guidelines /Council Directives Nr. 2006/42/EC and 2006/95/EC and the USDA-Regulations.

F&L GmbH Partner für Hygiene & FördertechnikLindenpark 16Tel: 033652-82280D- 15898 Neuzellewww.flnet.dewww.flnet.deFax: 033652-822827info@flnet.deFax: 033652-822827





Art.-Nr.: 1.560.02

technical data:

power supply: voltage control: performance: protection type: water supply: water outlet: cleaning time: temperature: weigth: dimensions: length: width: heigth: 400V/3/50 24 V DC 0,25 KW IP 65 R 1/2" HT- pipe DN 50 5- 10 s/ sole min. 4°C max. 40°C 65 Kg

849 mm 806 mm 1.057 mm





F&L GmbH Partner für Hygiene & FördertechnikLindenpark 16Tel: 033652-82280D- 15898 Neuzellewww.flnet.dewww.flnet.deFax: 033652-822827info@flnet.deFax: 033652-822827