

Hooks washing machine  
for 600 hooks / h  
electrical

Art.-Nr.: 1.614.20



### **Eurohooks washing machine**

The machine is created for washing euro hooks. The washing process is performed by water circulation in a closed filtered cycle incl. a suitable detergent. General water supply is used for rinsing. The duration of the washing and rinsing programmes can be adjusted by the operator. The detergent must be manually filled in to the tank (option). The tank which is under the wash zone is in filter equipped for catching bigger particles. The water (water solution) is heated by electro heating system. The temperature can be adjusted in limits of 30-65°C by thermostat. The rinse water is also used to complete and refresh detergent solution in main tank. The euro hooks must be hanged and then they are transported through different zones. The steering panel can be on the left or right side. The centrifugal pump will not run without liquid. Machine complies EU Council Directives Nr. 98/37/EEC, 73/23/EEC and the USDA Regulations.

Art.-Nr.: 1.614.20

**Technical data:**

Power supply:	400V(3L, N, PE), 50Hz
Total power:	16,5 kW
Pumps power:	2,2 kW
Heating:	2 x 7kW
Gear engine:	0,18 kW
Protection type:	IP65
Engines protection type:	IP55
Pump pressure:	3bar
Pumps performance:	12,3m <sup>3</sup> /h
Water outlet pressure:	3 bar
Water outlet:	DN50
Water inlet for washing:	R " 3/4
Water inlet for rinse:	R " 1/2
dimensions:	length: 3.140mm width: 1.060mm height: 1.800mm
weigh:	~450Kg

