

Hooks washing machine  
for 600 hooks / h  
steam

Art.-Nr.: 1.614.21



### **Hooks washing machine**

The machine is created for washing euro hooks. The washing process is performed by water circulation in a closed filtered cycle incl. a suitable detergent. General water supply is used for rinsing. The duration of the washing and rinsing programmes can be adjusted by the operator. The detergent must be manually filled in to the tank (option). The tank which is under the washine zone is in filter equipped for catching bigger particles. The water (water solution ) is heated by steam injectors. The temperature can be adjusted in limits of 30-65°C by thermostat. The rinse water is also used to complete and refresh detergent solution in main tank. The euro hooks must be hanged and then they are transported through diffrent zones. The steering panel can be on the left or righth side. The centrifugal pump will not run without liquid. Machine complies EU Council Directives Nr. 98/37/EEC, 73/23/EEC and the USDA Regulations.

Art.-Nr.: 1.614.21

**technical data:**

power supply:	400V(3L, N, PE), 50Hz
total power:	2,5 kW
pumps power:	2,2 kW
heating:	steam 3-12 bar, 135 C°
gear engine:	0,18 kW
protection type:	IP65
engines protection type:	IP55
pump pressure:	3bar
performance:	12,3m <sup>3</sup> /h
pressure by water outlet:	3 bar
water outlet:	DN50
washing water inlet:	R " 3/4
rinse water inlet:	R " 1/2
dimensions:	length: 3.140mm width: 1.060mm height: 1.800mm
weight:	~450Kg

