



Lifting and tipping  
1050-1550 mm  
for 120 L eurobin DIN9797  
left side, stationary

Art.-Nr.: 4.000.05

### Lifting / tipping device 1050-1550 mm, 120L eurobin/ buggy

The device is created for light, comfortable lifting and tipping of eurobins/buggies DIN 9797.

The device consists of a column, an engine with brake, drive (with two chains) and fork (the fork can be straight or rotated)

The devices are made of stainless steel 1.4301, except for a pusher, chains and its circles.

The safety system is a standard construction (two chains).

The lifting and tipping devices can be stationary or mobile (only by max. tipping height up to 2550 mm), left or right construction.

By tipping height over 3050 mm the devices have to be attached to the wall or ceiling

The machines are according to EU-guidelines /Council Directives Nr. 2006/42/EC and 2006/95/EC and the USDA-Regulations.

Art.-Nr.: 4.000.05

**technical data:**

Tipping height:	1050-1550 mm ( adjustment 5x 100 mm )
Power supply:	3 x 400/ 50 Hz
Control voltage:	24 V AC
performance:	0.8 kW
protection type:	IP 65
speed:	5 m/min
length:	937 mm
width:	325 mm
forks width :	1.013mm
total heigth:	2.490 mm

