



Lifting / tipping
2050-2550 mm
for 120 L eurobin DIN9797
left side, stationary

Art.-Nr.: 4.004.05

Lifting / tipping 2050-2550 mm, 120L eurobin / buggy

The device is created for light, comfortable lifting and tipping of eurobins/buggies DIN 9797.

The device consists of a column, an engine with brake, drive (with two chains) and fork (the fork can be straight or rotated)

The devices are made of stainless steel 1.4301, except for a pusher, chains and its circles.

The safety system is a standard construction (two chains).

The lifting and tipping devices can be stationary or mobile (only by max. tipping height up to 2550 mm), left or right construction.

By tipping height over 3050 mm the devices have to be attached to the wall or ceiling

The machines are according to EU-guidelines /Council Directives Nr. 2006/42/EC and 2006/95/EC and the USDA-Regulations

Art.-Nr.: 4.004.05

technical data:

| | |
|-------------------|----------------|
| power supply: | 3 x 400/ 50 Hz |
| Voltage control: | 24 V AC |
| performance: | 0.75 kW |
| Protection type: | IP 65 |
| speed: | 5 m/min |
| length: | 937 mm |
| Width | 325 mm |
| Width with fork : | 1.013mm |
| Total height: | 3.490 mm |

